

Harbour电缆与其它厂家电缆对照表

LL335i交叉型号对应表

	LL335i		UFB311A		32051		CF300		CXN3450		CXN3508		SUCOFLEX_106		IW2801	
总体直径 (mm)	7.62		7.90		7.62		7.87		7.4		8.1		7.9		7.75	
衰减值 (dB/m)	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max
@ 400 MHz	0.079	0.115	—	—	0.108	—	0.08	—	—	—	—	—	0.131	0.144	—	—
1GHz	0.157	0.180	0.160	—	—	—	0.13	—	—	—	—	—	0.217	0.238	0.15	—
2GHz	0.223	0.256	—	—	—	—	0.19	—	0.22	—	0.2	—	0.321	0.353	0.2	—
3GHz	0.275	0.311	—	—	—	—	0.24	—	—	—	—	—	0.407	0.448	—	—
5GHz	0.338	0.410	—	—	—	—	0.32	—	—	—	—	—	0.555	0.61	0.33	—
10GHz	0.557	0.623	0.490	—	—	—	0.48	—	0.5	—	0.46	—	0.859	0.944	0.49	—
18GHz	0.721	0.852	0.690	—	0.820	—	0.69	—	0.68	—	0.63	—	1.269	1.395	0.66	—

SS402 交叉型号对应表

	SS402		EZ FLEX 402		TFLEX-402		MULTIFLEX-141	
总体直径(mm)	4.14		4.140		4.06		4.14	
衰减值(dB/m)	Typ	Max	Typ	Max	Typ	Max	Typ	Max
@ 400 MHz	0.233	0.262	—	—	—	—	0.247	0.272
1GHz	0.367	0.426	—	—	0.380	—	0.401	0.441
2GHz	0.541	0.607	0.551	—	0.564	—	0.583	0.642
2.4GHz	0.590	0.656	—	—	—	—	—	—
3GHz	0.689	0.754	—	—	0.722	—	0.730	0.803
5GHz	0.885	0.984	—	—	—	—	0.974	1.071
10GHz	1.344	1.475	1.391	—	1.480	—	1.459	1.605
18GHz	1.902	2.098	2.000	—	2.165	—	2.085	2.294

SS405 交叉型号对应表

	SS405		EZ FLEX 405		Tflex-405		MULIFLEX-086	
总体直径(mm)	2.64		2.540		2.64		2.65	
衰减值(dB/m)	Typ	Max	Typ	Max	Typ	Max	Typ	Max
@ 400 MHz	0.443	0.459	—	—	—	—	0.465	0.488
1GHz	0.711	0.098	—	—	0.692	—	0.746	0.783
2GHz	0.951	1.049	1.033	—	1.000	—	1.072	1.125
2.4GHz	1.082	1.148	—	—	—	—	—	—
3GHz	1.213	1.279	—	—	1.250	—	1.329	1.395
5GHz	1.541	1.705	—	—	—	—	1.748	1.835
10GHz	2.262	2.623	2.463	—	2.460	—	2.447	2.685
18GHz	3.115	3.607	3.411	—	3.477	—	3.563	3.741

LL142 交叉型号对应表

	LL142		SFT-142		UFB142A		SUCOFLEX_103		CXN3449		IW1801	
总体直径 (mm)	4.95		4.57		3.61		4.60		4.8		4.83	
衰减值 (dB/m)	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max
@ 400 MHz	0.170	0.213	0.209	—	—	—	0.18	0.2	—	—	—	—
1GHz	0.269	0.328	0.333	—	0.330	—	0.291	0.319	—	—	0.250	—
2GHz	0.370	0.459	0.474	—	—	—	0.415	0.456	0.34	—	0.38	—
3GHz	0.459	0.557	0.584	—	—	—	0.513	0.563	—	—	0.46	—
5GHz	0.590	0.689	0.761	—	—	—	0.67	0.735	—	—	0.6	—
10GHz	0.820	0.984	1.094	—	1.080	—	0.968	1.062	0.78	—	0.850	—
18GHz	1.180	1.311	1.494	—	1.440	—	1.331	1.461	1.06	—	1.200	—

LL235 交叉型号对应表

	LL235		UFB205A		32055		CF210		SFT205		SUCOFLEX_104		IW2301	
总体直径 (mm)	5.97		5.21		5.46		5.59		5.21		5.5		5.59	
衰减值 (dB/m)	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max	Typ	Max
@ 400 MHz	0.151	0.164	—	—	0.157	—	0.06	—	0.174	—	0.148	0.162	—	—
1GHz	0.243	0.262	0.230	—	—	—	0.12	—	0.277	—	0.236	0.26	0.24	—
2GHz	0.348	0.374	—	—	—	—	0.2	—	0.395	—	0.338	0.372	0.3	—
3GHz	0.430	0.459	—	—	—	—	0.27	—	0.487	—	0.418	0.46	0.37	—
5GHz	0.564	0.590	—	—	—	—	0.41	—	0.635	—	0.548	0.602	0.5	—
10GHz	0.820	0.885	0.750	—	—	—	0.73	—	0.915	—	0.795	0.875	0.72	—
18GHz	1.118	1.213	1.050	—	1.148	—	1.22	—	1.255	—	1.11	1.211	0.95	—